gedore-automotive.com

GEDORE

KLANN EXPERIENCE

159 Top deals

NEW

The stationary GEDORE spring compressor now with mobile work stand!

Page 2-3



NEWS + PROMOTION 01.01. - 31.08.2024

MISSION: KLANN POSSIBLE

Time saving, safe, well thought out tools.

OPERATION BOARD







TIME SAVING

These tools especially save time and thus real money.



SAFE WORK

With these tools, the focus is particularly on safety during use



ONLY FROM GEDORE

These tools are protected by us by patent, utility model, or design patent



MATERIAL-PROTECTING

These tools protect vehicle of spare parts from damage during removal and installation



COMMERCIAL VEHICLES

These tools are especially developed and suited for the use on commercial vehicles



TRANSPORTERS


These tools are especially developed and suited for the use on transporters



PASSENGER CARS

These tools are especially designed and suitable for use on passenger cars







Universal fit for nearly all McPherson spring struts on the market.

Fits particularly for right or left rising springs, conical springs, eccentric springs, springs with a low number of coils, springs with a high or varying spring pitch, spring struts with pulling shocks as well as for spring struts with electronic control and sensors.

- UNIQUE, QUICK and SAFE, simply BETTER!
- Tensions even the strongest springs **EV VEHICLES**
- Damage-free holding over the damper tube
- Safe tensioning directly via the shock top bearing
- Spring form and pitch completely irrelevant
- No intervention into the spring necessary
- Maximum user safety
- Simplest handling
- One-man operation
- High load capacity
- 4-way safety




Code	No.	Drive	Breaking point	Max. load:	Max. span	Spring collar diameter	Weight
3230503	KL-5501 B	SW 24	60 000 N	15 000 N	570 mm	125 - 220 mm	46 kg

KL-5501-500

MOBILE WORK STAND for KL-5501 B

• For making the spring compressor mobile

compact dimensions



Code	No.	Design	Width	Height	Depth	Weight
3462242	KL-5501-500	adjustable	700 mm	605 mm	730 mm	35 kg















HAND CRANK

releasing a McPherson strut

KL-5501-40



• The hand crank enables a simple and convenient drive of the stationary spring compressor

KL-5501 or KL-5501 B when compressing and











KL-5501-1435 A

ADAPTER RING

Fits spring struts with fork type mounting.

• Enables the safe holding of suspension struts with fork type mounting on the lower support of the stationary spring compressor KL-5501 / KL-5501 B





Code





Made in Germany



No.

KL-5501-1435 A





Adapter Ø

57 mm







20 mm





No.

KL-5501-40





Drive (hexagon)





Length

195 mm



KI-5501-31

COLLAR MOUNTING KIT

Suitable for Renault Clio IV (Type X98); Nissan Qashqai II (J11), VW (MEB platform).

- Enables the safe holding of the shock top mount on the spring compressor KL-5501 / KL-5501 B
- Easy placing of the adapter on the spring collar
- Inner diameter of the adapter 60 / 90 mm



Code	No.	Thickness	Inner Ø 1	Inner Ø 2
3406059	KL-5501-31	10 mm	60 mm	90 mm

KI-5501-210

Code

ASSEMBLY KIT

for KL-5501 B, adjustable



Suitable for the stationary spring compressor KL-5501 B.

- For mounting the spring compressor on a MODULO trolley (KL-4999-12x A / 1507 XL)
- Height-adjustable in three positions
- Wall mounting possible, but then the use of the hand crank of KL-5501-40 is inconvenient.





Code	No.	Design	Distance drive to the wall	Weight
3461068	KL-5501-210	adjustable	105 mm	10 kg











4parts





















KL-5501-212

WALL BRACKET long

Fits KL-5501 B (NOT for KL-5501).

- The long wall bracket enables stable mounting of the stationary spring compressor KL-5501 B to a vertical wall
- Allows use of hand ratchet as well as the hand crank KL-5501-40



	Code	No.	Distance between wall and the centre of the drive	Weight
3	3402169	KL-5501-212	245 mm	3.5 kg


KL-5501-1431

PLASTIC SUPPORT

for shock absorbers

• For modification of the KL-5501 spring compressor to the newer version of the support plate





Code	No.	Overall height	Outside diameter	Weight
2793520	KL-5501-1431	47 mm	100 mm	180 g



























KL-5501-191

CONVERSION KIT compress unit, long

Fits KL-5501.

- Enables securing of complex shock absorbers which have a very small mounting surface on the shock absorber tube
- By using KL-5501-191 and KL-5501-192, KL-5501 can be converted to KL-5501 B



Code	No.	Weight
3244032	KL-5501-191	2.8 kg

KL-5501-192 **CONVERSION KIT**

for the support

Fits KL-5501.

- Enables the extended adjustment of the lowersupport
- By using **KL-5501-191** and KL-5501-192, KL-5501 can be converted to KL-5501 B



Code	No.	Weight
3244059	KL-5501-192	3 kg

KL-0056-11 EA

SHOCK ABSORBER PISTON ROD TOOL KIT

with foam insert

Fits universally for McPherson struts on passenger cars.

• For quick loosening and tightening of the the piston rod nut on McPherson struts.

Advantages:

- Holder with 5/16" bit drive
- Holder with 1/4" socket drive
- Open 12 point sockets

Suitability: universal















Code

Content Socket, open SW 16-21 mm | holder for 5/16" bits and 1/4"sockets, KL-0056-11 EA Screwdriver bit SW 5-7 mm, T50, XZN12I 2-point socket, 6-8 mm | open-ended spanner with ring ratchet 19 mm Weight 1.5 kg

KL-0050-510 A

SHOCK ABSORBER PISTON ROD TOOL KIT















Fits Mercedes C-Class (W203) and CLK (W209) front axle.

• For loosening and tightening the shock absorber piston rod nut (locknut)





2parts

Code No. KL-0050-510 A



Shock absorber lock nut spanner (Mercedes) I insert, Allen key, SW 7

KL-0050-51 A shock absorber lock nut spanner (Code 3448568) same as KL-0050-510 A but without the Allen key insert

Weight

160 g

REMOVAL AND INSTALLATION TOOLS

Made in Germany













for McPherson suspension struts

Suitable for McPherson suspension struts in combination with the vehicle-specific supplementary kits.

TIME, COST-SAVING and EFFICIENT, simply HELPFUL!

• Unique special device for compressing or reducing the overall length of the suspension strut

 Enables an extremely quick removal and installation of McPherson suspension struts, particularly for vehicle axles with suspension strut clamping holes

• Extremely high time and cost savings, as there is no need to loosen axle parts and no wheel alignment is required

Spring shape and spring pitch are completely irrelevant here

- No intervention in the spring necessary
- Maximum user safety
- Simplest handling
- · High load capacity
- 4-fold safety

Necessary accessories:

Vehicle-specific supplementary kits - KL-0029-1..



VW AUDI SEAT

ŠKODA BMW FORD



^{* =} without support plate

KL-0029-110 A

SUPPLEMENTARY KIT VW-AUDI

Size 1, size 2, size 3























Fits VW-Audi, Seat, Škoda vehicles on MQB, PQ25, PQ35, and NSF platform.

- For easier removal of the suspension strut
- Only in combination with the spring preloading basic tool **KL-0029-100 / -200**

Suitability: VW AUDI SEAT SKODA

 Code
 No.
 Content
 Weight

 3127850
 KL-0029-110 A
 1x KL-0029-111 - Support plate, size 1l 1x KL-0029-120 A - Supplementary kit, size 2l1x KL-0029-130 A - Supplementary kit, size 3
 3.5 kg

KL-0029-160 A

7parts

SUPPLEMENTARY KIT



















Fits BMW front axle suspension struts, for example, BMW 3 Series (E46 / E90 / E91 / E92); 5 Series (E39 / E60 / E61); 1 Series (E81 / E87); X1 (E84).

- For easier removal of the suspension strut
- Only in combination with the spring preloading basic tool **KL-0029-100 / -200**

Suitability: BMW

Code	No.	Content	Size	Weight
3275221	KL-0029-160 A	Support plate size 6 with boltl Support ring size 6	6	2.3 kg



























KL-0029-150

SUPPLEMENTARY KIT

Ford, size 5

Suitable for Ford front axle suspension struts. Installed in, for example, Ford Mondeo IV (BA7), S-Max (WA6), and Galaxy (WA6).

• For easier removal of the suspension strut

• Only in combination with the spring compressor base unit

• KL-0029-100 / -200





4parts

Code	No.	Content	Size	Weight
3077233	KL-0029-150	Support plate size 5 with bolt support ring size 5l 2 extension sleeves	5	3.6 kg

KL-0029-152

SUPPLEMENTARY KIT

Ford, size 8

Fits Ford front axle suspension struts, for example, Ford Kuga I and Kuga II (DM2).

• For the quick removal and installation of the McPherson strut

· Only in combination with the basic tool

KL-0029-100 / -100 A







3 parts	
----------------	--

Made in Germany

Made in Germany

Code	No.	Content	Size	Weight
3419290	KL-0029-152	1x Support ring size 51 1x Complementary kit Ford, size 8, small	8	2.5 kg

KL-0104-21 KB

ADJUSTABLE SPREADING TOOL

with wedges (Nos. 1 + 2 + 4 + 5)

Suitable for strut clamping holes and support joint mounts.

• Enables the professional widening of the strut clamping hole or the lower suspension joint mounting

• To pull out stuck shock absorber units or suspension joints without damaging them

Advantages:

6parts

- No slipping of the spreading tool!
- No over-expansion of the strut clamping hole thanks to expansion wedges with stop!
- No damaging of the cast metal or aluminium steering knuckle housing!
- Off-centre camping slots are no problem!











Code	No.	Spreading dimension	Weight
3269396	KL-0104-21 KB	Wedge 1: a=5.5 mm, b=12.0 mm / wedge 2: a=2.0 mm, b=8.0 mm / wedge 4: a=5.5 mm, b=9.5 mm / wedge 5: a=12.5 mm, b=17.0 mm	1.75 kg

KL-0033-10 E Z

INTERNAL-TYPE SPRING COMPRESSOR

compact, with size 2A and OA

Universal fit for chassis springs on transverse and trailing arm axles, for example on Audi A4 B8 (8K), A5 (8T), A6 (C7 /4G), A7 (C7 /4G), Q5 (8R); Mercedes-Benz E-Class (W211, W212), C-Class (W204), GLA (X156), GLK (X204); Ford Focus II (MK2); BMW 1 Series (E81); VW Passat (B8/3G).

- Enables the quick and safe removal and installation of chassis springs
- For very small through holes (approx. 34 mm dia.) in the wishbone

Advantages:

- Very compact design (approx. 34 mm diameter)
- No wheel alignment necessary
- Very high time saving
- Very safe compressing due to 3-point safety locking
- no sudden moving of the spring while compressed

Recommended accessories:

KL-0033-300 E- Hold-down device kit with foam insert

Suitability: universal, especially for:



L	VW AUDI	MERCEDES	BMW PORSCHE FORD
1	Code	No.	Max. load:





For spring diameter





SPRING AND STRUT CHANGE



Fits universally for chassis springs on wishbone and multi-link axles, for example on VW-Audi, Porsche, Mercedes, BMW, Ford, etc.

- Facilitates the disassembly and installation of chassis springs on wishbone and multi-link axles
- The multi-link remains in original position for more room
- Increases space for spring replacement

Suitability: universal, especially for:

VW AUDI PORSCHE

MERCEDES BMW FORD

Code No. Drive Diameter of support Compression distance (adjusting nut, short) Compression distance (adjusting nut, long)

3275205 KL-0033-300 E SW 22 40/50 mm 80 - 113 mm 105 - 138 mm

Made in Germany

KL-8041-300

PREMIUM WHEEL BEARING PACKAGE



Universal fit.

- For a professional removal and installation of wheel bearings, wheel hubs and cardan shafts
- Even extremely stuck or rusty wheel bearings, can be easily pulled off with the hydraulic cylinder

Necessary accessories: Hydraulic pump

Code	No.	For Ø (min.)	For Ø max.	Drive	Content
3434974	KL-8041-300	60 mm	85 mm	mechanical hydraulic	Wheel bearing tool kit, wheel hub puller kit, impact extractor 4.8 kg, supplementary kit for drive shafts, hydraulic drive, hydraulic cylinder 17 t

Made in Germany

KL-8041-400

PREMIUM WHEEL BEARING PACKAGE



Suitable for the removal and installation of wheel hub bearing units with Ø 72 / 78 / 82 / 85 mm, e.g. for VW, Audi, Seat, Skoda, Ford, Mazda, Volvo, etc.

- For professional removal and installation of wheel hub bearing units
- Particularly powerful thanks to the 17 t hydraulic cylinder



Code	No.	Drive type	Load (max.)	Weight
3449823	KL-8041-400	hydraulic	12 t	29 kg

PREMIUM WHEEL BEARING PACKAGE

















Suitable for the removal and installation of wheel hub bearing units with Ø 72 / 78 / 82 / 85 mm, e.g. for VW, Audi, Seat, Skoda, Ford, Mazda, Volvo, etc.

- For professional removal and installation of wheel hub bearing units
- Particularly powerful thanks to the 17 t hydraulic cylinder



Code	No.	Drive type	Load (max.)	Storage	Weight
3449831	KL-8041-400 E	hydraulic	12 t	with foam insert	30 kg

Made in Germany

KL-0041-452 C

WHEEL-BEARING MOUNTING TOOL

85 mm diameter

Suitable for rear axles with wheel bearing Ø 85 mm, for example on Toyota ProAce; Peugeot Expert, Traveller; Citroen Jumpy, etc.

- For removal and installation of the wheel bearing unit directly on the vehicle
- Required for wheel hubs without centre bore
- No damage to the bearing, as pressure during installation is only applied via the outer bearing ring

Additional mechanical drive parts necessary! KL-0040-2500 - Hydraulic cylinder, 17 t KL-0039-802 - Hydraulic drive KL-0041-380 A - Wheel hub extractor KL-0215-35 M25 - Hand pump

Suitability:

TOYOTA | PEUGEOT CITROËN







1	Coae	No.	for outside diameter (bearing)	Hole circle Ø	Load (max.)	νrive type
	3445828	KL-0041-452 C	85 mm	5x108 5x112	17 t	hydraulic

KL-0041-4521

PULLER PLATE WITH SCREWS





Accessory necessary! KL-0041-380 A - Wheel hub extractor KL-0041-451 B and KL-0041-461 D -Wheel bearing mounting tool

Made in Germany

Suitable for rear axles with wheel bearing Ø 85 mm, for example on Toyota ProAce; Peugeot Expert, Traveller; Citroen Jumpy; Opel Zafira, Vivaro, Renault Traffic, Fiat Talento etc.

- For removal of the wheel bearing unit directly on the vehicle
- Required for wheel hubs without centre bore
- As supplement for MODULO KL-4999-250 / -260 / -270 as well as previous models

Suitability: TOYOTA PEUGEOT CITROËN RENAULT OPEL FIAT

Code	No.	Outside diameter	Drive type	Height
3445836	KL-0041-4521	135 mm	hydraulic	35 mm

9

KL-0041-380 EA

WHEEL HUB EXTRACTOR

with foam insert

Universally fits wheel hub / wheel bearing units, wheel hubs, and wheel bearings with a diameter of up to 250 mm.

For pulling out wheel hub bearing units
 For pulling out wheel hubs and wheel had

 For pulling out wheel hubs and wheel bearings from the wheel bearing housing

Construction withstands up to 12 tons design

 Even glued, stuck or rusty wheel hub bearing units, wheel hubs and wheel bearings do not pose a problem

• Drive with the 17t hydraulic cylinder







Code

No. KL-0041-380 EA Max. span width

Max. load:

Made in Germany

Made in Germany

* in combination with thrust spindle (1.2606280KS)

12t*

7 t

KL-0041-384

BOLTED BEARING SUPPORT


Universally suitable for 3rd generation screwed wheel bearing units on passenger cars and commercial vehicles.

• For professional extraction of tight-fitting wheel bearing units directly on the vehicle

• Only in conjunction with wheel hub extractor **KL-0041-3800 C(KL-0041-380 EC**)







4parts

NOTE:Available as of February 2024.

4parts Available as of February 202

Drive type

Load (max.)

12 t

KL-0040-2500

HYDRAULIC CYLINDER 17T

















- The hollow-piston cylinder is suitable for pulling and
- Applicable for the removal of installation of cardan shafts, silent blocks and suspension joints

Necessary accessories: Hydraulic pump

Suitability: universal

Code	No.	Max. admissible force:	Max. stroke	Oil pressure (max.)	Thread with hollow piston	Fastening thread thrust side	Fastening thread pull side	Outer diameter of cylinder	Overall cylinder height retracted/ extended:	Connection thread for hydraulic coupling	Weight
1751441	KL-0040-2500	170 kN (17 t)	45 mm	700 bars	M20	2¼"-14 UNS	M42x2	80 mm	202 - 247 mm	3/8"NPT	5.7 kg

SUPPORT DEVICE FOR HYDRAULIC CYLINDER

• Enables easy positioning of the hydraulic cylinder **KL-0040-2500** on a gearbox jack (ram Ø 30 mm)







Code	No.	Mounting Ø	Inner diameter	Drive type	Weight
2707497	KL-0040-258 A	30 mm (gearbox jack)	80 mm	hydraulic	2.5 kg

Made in Germany



KL-4999-250 / KL-4999-260 / KL-4999-270 A

ASSEMBLY TROLLEY MODULO

The mobile workplace for wheel bearing and silent block - repairs


The hand tools and drive parts included in the trolley mean that the tools required for the application are available at any time. No additional hand tool trolley is required.

Additionally, it offers an ideal work surface with its large, solid multiplex countertop. The drawers are equipped with individual pull-out stops and full extension.

Dimensions: W 1.200 x H 985 x D 635 mm



MODULO KL-4999-250 / -260 / -270 /



MODULO FOR AXLE REPAIRS:

Once invested perfectly equipped for the future!



Drive shaft and wheel bearing/hub



Wheel bearing inner race

- Pulling off bearing inner race
- for example wheel bearing 1st and 3rd generation









Drive shaft

- Pressing out the drive shaft from the wheel hub
- Inserting the drive shaft into the wheel hub











1. Generation wheel bearing

- Pulling off wheel hub
- Removal and installation of wheel bearing
- Installation of wheel hub
- for example also Mercedes Vito/ Viano HA, Audi Q7 HA









2. Generation wheel bearing

- Removal and installation of wheel hub bearing units
- with and without spring ring
- without load on the new wheel bearing during installation
- for example VW-Audi, Ford, Mazda, Volvo, ...









3. Generation wheel bearing

- Removal of stuck wheel hub bearing units
- Removal of extremely stuck wheel hub bearing units with **Subaru**, etc.







Silent block and ball joint



Ball Joint Separation

- Breaking of ball joint connections
- for example suspension joint, track rod, etc.









Ball joint

 Removal and installation of ball joints directly on the vehicle





270 A





Silent block

- Removal and installation of silent blocks directly on the vehicle
- · With and without press frame








AXLE REPAIR

MODULO ASSEMBLY TROLLEY

KL-4999-250

"MODULO 250" ASSEMBLY TROLLEY





The assembly trolley is the ideal mobile workstation for fast, organised, and efficient repairs on under carriage of vehicles.

Content / range of application:

- Various drive parts for operating the tool kit
- Removal and insertion of wheel bearings and hubs
- Removal and insertion of wheel hub bearing units
- Separating of wishbones from the support joint clamping hole
- Removal of bonded and jammed ioint shafts
- Various helpful hand tools

Required drive parts:

KL-0215-35 M25 - Hydraulic pump

Suitability: universal

127parts Load-carrying capacity of drawer



KL-4999-260

"MODULO 260" ASSEMBLY TROLLEY



The assembly trolley is the ideal mobile workstation for fast, organised, and efficient repairs on under carriage of vehicles. Content / range of application: • Various drive parts for operating the tool kit

- Removal and insertion of wheel hub bearing units
- Separating of wishbones from the support joint clamping hole
- Removal and insertion of wheel bearings and hubs
- Removal of bonded and jammed joint shafts
- Pulling and forcing into place of support/guide joints, silent blocks and joint bearings
- Pulling of stuck screwed wheel bearing units
- Also suitable for Subaru wheel bearings as well as Ford/Mazda/Volvo silent blocks rear axle
- The universal solution for nearly all axle repairs
- Various helpful hand tools

Required drive parts:

KL-0215-35 M25 - Hydraulic pump

Suitability: universal



189parts

Load-carrying capacity (static / dynamic) Load-carrying capacity of drawer KL-4999-260 1,000 kg / 750 kg 70 kg





- The hydraulic hand pump can be used as a drive for the KL-0040-2500 or KL-0040-1700
- The ton scale allows to check the hydraulic pressure and

Suitability: universal

Pressure (max.) KL-0215-35 M25



KL-0215-36 M25 **FOOT PUMP**

(pneumatic)



- Can be used for hydraulic cylinder drive
- Compressed air is used as driving
- Foot pedal with three positions for pumping, holding and relieving
- Both hand are free for the work

Suitability: universal

Code	No.	Pressure (max.)	0perat
2478706	KL-0215-36 M25	700 bars	8























hydraulic cylinders

Drive type

the required power during the work

71	
manual / hydraulic	7.5 kg

Weight



"MODULO 270 A" **ASSEMBLY TROLLEY**

The assembly trolley is the ideal mobile workstation for fast, organised, and efficient repairs on under carriage of vehicles.

Content / range of application:

- Various drive parts for operating the tool kit
- Removal and insertion of wheel bearings and hubs
- Removal and insertion of wheel hub bearing units
- Separating of wishbones from the steering knuckle clamping hole
- Removal of bonded and jammed joint shafts
- Pulling and forcing into place of support/guide joints, silent blocks and joint bearings
- Pulling of stuck screwed wheel bearing units
- Counter-holding of wheel hubs when loosening and tightening the wheel bearing central bolt
- Pulling of stuck wheel bearing inner rings from the wheel bearing
- Compressing of ear O-clips and locking of stepless hose clips
- Separating of ball joint connections on steering and axle systems
- Loosening and tightening of inner tie bar joints or axial joints
- Also suitable for Subaru wheel bearings as well as Ford/Mazda/Volvo silent blocks rear axle
- The most comprehensive solution for almost any axle repair
- Also for removing inner ring bearings and breaking breaking of ball joints on passenger cars and light commercial vehicles
- Various helpful hand tools
- · Reshaping of stud bolt threads at the wheel hub
- Inserting cardan shafts

Suitability: universal

Including Hydraulic-Pump





Load-carrying capacity (static / dynamic) Load-carrying capacity of drawer KL-4999-270 A 1,000 kg / 750 kg



ng pressure Drive type 12 bar pneumatic / hydraulic



ECCENTRIC WRENCH

Made in Germany













for removal and installation of the axial joint



Fits universally for cars and vans.

• For the quick removal and installation of internal track rod or rod or axial joints with a Ø of 30 - 43 mm

Advantages:

- High time saving
- Without removing the steering gear
- Unique open construction
- Resistant profiling reliably prevents reliable slipping of
- Direct mounting on the tie rod
- Drive via 1/2" square socket

Code	No.	Drive	For Ø (min.)	For Ø max.
3427900	KL-0167-30 A	1/2"	30 mm	43 mm

KL-4007-3270

EXTENSION 700 MM, 1/2"













Universal fit.

- Especially suitable for KL-0167-30 / -30 A
- For hand-operated socket spanners
- With ball lock.

Code	No.	Drive/output	Length	Weight
3447707	KL-4007-3270	1/2"	700 mm	920 g

KL-0121-96 B

1/2"

CLAMPING PLIERS









Made in Germany














 For professional closing of stainless-steel pinch clamps and tension clamps

Advantages:

- Torque tightening possible
- Including exchangeable pliers fingers
- Pliers fingers can be mounted at the FRONT or at the SIDE

Suitability: universal, especially for:





Code	No.	Length	Drive	Weight
3410129	KL-0121-96 B	260 mm	3/8"	500 g

KL-0121-9611

16

CHANGEABLE JAW KIT WITH HOOKS





Length







Width







Weight 80 g









- For closing of special hose clips
- In combination with KL-0121-96 A

















Fits VW-Audi, Seat, and Škoda vehicles with multi-link axle.

BORING TOOL KIT VW-AUDI

• For fast and professional drilling of extremely jammed clamping screws (size 16)

• Required, for example, when changing the upper or lower suspension arms and the tie bar end
• No replacement of the steering knuckle required

Suitability:

VW AUDI SEAT ŠKODA



14parts

Code No.

KL-0250-43 KB

Drill Ø 1

Drill Ø 2





391 x 304 x 134 mm



WHEEL CHANGE KIT

















- For the controlled tightening of bolts
- R68900200: controlled and precise screw tightening from 40 to 200 Nm
- With test certificate according to DIN EN ISO 6789
- R60010027: Can be extended in five stages from 460 mm to up to 600 mm
- R63043003: In SW 17, 19 and 21 with colour coding
- In accordance with DIN 3120 C12.5, ISO 1174, with ball lock
- Design according to DIN 3129, ISO 2725-2



Code

R69003000

Content

R68900200 Torque wrench 1/2" 40-200 Nm | R60010027 2K telescopic ratchet 1/2" reversible | R63043003 Power socket kit 1/2" 3-piece

3549 UK

TORCOFLEX UK TORQUE WRENCH

5-50 N·m















- Adjustable, releasing and robust tubular torque wrench with integrated lever-operated ratchet with square drive
- Classified to DIN EN 6789: 2017 type II class A calibrated to a max. admissible deviation of +/-3% and therefore more precise than +/-4%required by the standard
- incl. test certificate according to DIN EN ISO 6789-2:2017
- For controlled clockwise tightening













Code	No.	Type	Square drive	Square drive metric	Nm	Distance housing - square centre	Length	Head width	Head height	Weight
2958015	3549-02 UK	Ratchet with lever switch	1/4"	6.3 mm	5-25	12.5 mm	286 mm	25.0 mm	21.5 mm	0.67 kg
2958023	3549-05 UK	Ratchet with lever switch	3/8"	10 mm	10-50	17.5 mm	348 mm	35.0 mm	19.1 mm	0.825 kg

Made in Germany
















5parts **1/2 (**



- Reliable torque wrench with a tightening range of 40-200 Nm with test certificate
- Controlled right-hand tightening; reversible ratchet with clockwise and anti-clockwise rotation; drive: 1/2"
- Classified to DIN EN ISO 6789-2:2017; Adjusted to a max. admissible deviation of +/-3 % and therefore more precise than +/-4 % required by the standard
- Through a 1/2" extension and power sockets with protective sleeve in sizes 17, 19, and 21 mm very suitable for changing wheels on passenger cars

Better readability by magnifying effect





Code	No.	Type	Square drive	Torque	Content	Height	Length	Head width	Head height	Weight
3107027	3550-UK-LS4	Ratchet with lever switch	1/2"	40-200 Nm	Torque wrench TORCOFLEX 40 - 200 Nm no. 3550-20 UK Extension no. 1990-5 Power screwdriver kit 1/2", , 3-part	44 mm	499 mm	42.5 mm	22 mm	2,4 kg

TT3KH

ELECTRONIC TORQUE KEY TORCOTRONIC III

GEDORE















- Torque and rotation angle measurement
- Documented clockwise and anti-clockwise tightening
- Software included
- 5 tightening parameters can be memorised
- 2000 storage spaces
- Measuring accuracy torque +/- 1 %, +/- 1 digit















• Measuring accuracy angle of rotation +/- 1 %, but at least +/- 1° to 360° at min. 4°/sec

0 3 4

- Programmable with different gauges for insertion tools
- Extremely simple operation, user-friendly icon menu navigation
- Easy to read, illuminated display
- Test certificate in accordance with factory standard GTTWN001
- Optional certificate in accordance with DAkkS-DKD-R 3-7

Code	No.	Туре	Drive	Nm	Length	Weight
2648636	TT3KH 120	Rectangular holder	1/2"	10-120	670 mm	1.2 kg
2648644	TT3KH 350	Rectangular holder	1/2"	70-350	900 mm	1.7 kg









- For unscrewing and tightening wheel bolts / release nuts
- Required for damaged chrome bolts/- nuts
- Half a spanner size smaller when chrome cap is missing
- Half a spanner size larger in case of extended chrome cap (corrosion)

Suitability: universal, especially for:

FORD JEEP RANGE ROVER

















Code	No.	Profile	Drive (square)	Storage	Weight
3427773	KL-0100-81 K	6-edge	1/2"	in case	1.5 kg



KL-0173-612 A

RETHREADING TOOL FOR WHEEL STUDS

(M12X1.5)

Universally applicable on wheel studs and wheel bolts with $\mbox{\tt M12x1.5}$ thread.

• Quick and cost-saving rethreading of damaged threads

- Thread is remoulded to its original geometry
- No material removal
- Strength of the wheel bolts/screws is retained
- Compact design
- Including pipe socket wrench SW 41
- Thread size covers approx. 80%
- For vehicles with wheel studs!





















KL-0173-601 A

RETHREADING TOOL KIT FOR WHEEL STUD THREAD (M12X1.25 + M14X1.5)

Universally applicable on wheel studs and wheel bolts with M12x1.5 as well as 14x1.5 thread, for passenger cars and vans.

• For description see KL-0173-612 A



KL-0173-622 A (M14x1.5)



KL-0173-611 A (M12x1.25)



Code	No.	Drive (hexagon)	Thread
3461904	KL-0173-601 A	41 mm	M12x1.25 + M14x1.5

RIM CLEANING DISC SET







For universal use on aluminium rims and other metallic surfaces.

- For easy removal of adhesive residues
- Easy to use with conventional axial grinders, cordless screwdrivers or drills
- \bullet Mounted using 5/16" internal thread or 9 mm external Ø

Code	No.	Receiving thread	Mounting Ø	Speed (min.)	Speed (max.)	Outside diameter	Weight
3463877	KL-0101-121	5/16"	9 mm	500 rpm	1000 rpm	60 mm	300 g

KL-0115-100 WHEEL HUB RIM GRINDER



Universal use on wheel hubs as well as steel and aluminium rims on cars and vans.

- For quick cleaning of the wheel hub as well the rim contact surface
- Solid corrosion residues can be easily removed



Code	No.	Drive (hexagon)	Speed (max.)	Outside diameter	Weight
3463893	KL-0115-100	7/16"	1500 rpm	160 mm	700 g

KL-0115-1001

WHEEL HUB REPLACEMENT DISC







In conjunction with the wheel hub/rim flange grinder **KL-0115-100**, for cleaning the wheel hub.



Co	ode	No.	Outside diameter	Inner diameter	Total weight
346	3907	KL-0115-1001	160 mm	75 mm	500 g

KL-0115-1002

RIM REPLACEMENT DISC







In conjunction with the wheel hub/rim flange grinder **KL-0115-100**, for cleaning the rim contact surface.



Code	No.	Outside diameter	Inner diameter	Total weight
3463915	KL-0115-1002	160 mm	50 mm	700 g

WHEEL HUB GRINDER FOR STUD BOLTS

























Universal use on wheel hubs on cars and vans with wheel studs.

- For quick cleaning of the rim contact surface
- Solid corrosion residues can be easily removed
- Patented quick-change holder for exact centring between the base body and grinding cone



Code	No.	Drive (square)	Outside diameter	Outer dia. (2)	Length	Weight
3463931	KL-0115-200	1/2"	50 mm	40 mm	110 mm	500 g


KL-0101-120

ADHESIVE WEIGHT REMOVER









- For easy removal of adhesive weights from aluminium rims
- Extremely flexible 3-sided plastic blade
- No damage to the paintwork
- Robust handle for use with a hammer





KL-0860-100

BRAKE FLUID TESTER

Can be used universally for conventional DOT 3, DOT 4 and DOT 5.1 glycol-based brake fluids.

- For professional checking of the water content in the brake fluid
- Fast and precise measurement of the water content in %
- High measuring range from 0.1 % to 6.0
- Simplest handling
- 2" LCD display with backlighting
- Optical and acoustic alarm function
- Measuring probe dust and water protected to IP67
- Power supply with 9 V battery (not included in the scope of delivery!)





Code	No.	Measuring range (min.)	Measuring range (max.)	Display size	Battery type	Length (cable)	Line diameter	Temperature range	Length	Weight
3467058	KL-0860-100	0.1 %	6 %	2.0"	9V block battery	270 mm	5.9 mm	-10 up to +50 ℃	450 mm	120 g

SET OF SOCKETS, BRAKES

No.

KL-0112-9





KL-0112-901= Audi, Porsche, Mercedes

KL-0112-902 = Audi S5

KL-0112-911 = Audi Q7

KL-0112-912 = Audi S8, Q7; Porsche Macan, Cayenne, Cayman

KL-0112-913 = Audi S6, A8; Porsche Cayenne

Recommended accessories: 1993 U-20 - Reversible ratchet

Number of teeth profile

10, 7, 7, 10, 10

KL-0114-55

 $O \cap \mathbb{Z}$ Code

UNIVERSAL BRAKE CALLIPER HOOK **PAIR** (shapeable/flexible)



Spanner size:

Universally applicable.

Height

50 mm

- Two flexibly shapeable hooks with a robust blue surface coating
- For example, they can be used for maintenance and repairs, to safely suspend brake callipers, air conditioning compressors, power steering pumps, and much more
- Damage to hoses and cables from hanging down can thus be avoided

Weight (total) Code No. Length 100 g

Drive







- For easy loosening of stuck hose connections
- Can also be used as a mini lever for other work



Code	No.	Length	Weight
3463982	KL-0126-303	240 mm	270 g


Made in Germany

KL-0121-38 C

PLIERS FOR FUEL LINE







- For easy unlocking of quick-release couplings on fuel hoses and urea lines
- Also suitable for hard-to-reach areas thanks to swivelling pliers fingers
- Slim and round pliers tips

Code	No.	For engine type	Swivel angle	Tip thickness	Length	Weight
3455831	KL-0121-38 C	Petrol / Diesel	180°	3.8 mm	270 mm	250 g



INJECTOR EXTRACTOR KIT

Made in Germany











Supplement to the pneumatic injector extractor





Universally fits Bosch and Siemens-VDO injectors with a removable fuel connection with M12x1 internal thread (45° angled). For example for VW-Audi, BMW, Mercedes, and PSA.

• For professional extraction of tight-fitting injectors

Made in Germany

- Thanks to extension kits KL-0186-9.. suitable for many other injectors
- Only in combination with KL-0186-80 K, KL-0369-4100, KL-0369-4111, or KL-0043-300

Suitability: MERCEDES | PSA | FORD | VW | AUDI | SEAT | ŠKODA | MAZDA | VOLVO |

Code	No.	for injectors	for female thread	Bracket	For engine type	Drive type
3461610	KL-0186-903	Bosch Siemens / VDO	M12x1	45°	Diesel	pneumatic

KL-0186-901 A

NOZZLE EXTRACTOR M12X1

with impact weight

Universally fits Bosch and Siemens/VDO injectors with a fuel connection female thread of M12x1/45°. Installed in many common passenger car engines.

- Required, for example, when replacing the injectors or removing the valve cover
- Opening the injector is not necessary for this purpose as the injector puller is fastened with the fuel connection by means of the special screws included in the kit.

Suitability: universal





11parts

Code No. for injectors for female thread Bracket For engine type Drive type KL-0186-901 A **Bosch Siemens / VDO** Diesel manual

INJECTOR PULLER KIT

Universal, in plastic case

Universal fit for BOSCH and DELPHI injectors with M17x1 female thread and M14x1.5 male thread, for example, on PSA, Fiat, Mercedes, VW-Audi, Renault, Nissan, Vauxhall/Opel, Toyota, etc.

• For quick and powerful pulling of heavily stuck diesel injectors

• No removal of the cylinder head required

• Supplementary kits for engines and injectors available

• Can be operated hydraulically (accessories required)

Suitability: universal, especially for:

MERCEDES VW AUDI FORD MAZDA PSA PEUGEOT | SUZUKI FIAT VOLVO

CITROËN



Made in Germany

for female thread Engine type Code for male thread Injectors KL-0186-14 KB Diesel Bosch, Delphi

KL-0186-1... SUPPLEMENTARY KITS

KL-0186-1281 A Siemens injector M25x1

Suitable for Siemens - injectors with an M25x1 female thread and a spanner size of 25 mm, e.g. for VW, Audi, Seat, Škoda 1.6 TDI. (CAYA, CAYB, CAYC, CAYD, CAYE, CLNA)

• Supplement for the injector extractor KL-0186-14 KB or KL-0186-80 K

• Depending on the engine, the specific support bolt kit



for injectors

Denso











KL-0186-1284 A

Denso injector M20x1

Suitable for Denso injectors with an M20x1 female thread and, additionally, M25x0.5 or M25x0.75 male threads and a spanner size of 27 mm.



• Depending on the engine, the specific support bolt kit KL-0186-123.. / -124.. may be required

No.

KL-0186-1284 A

	5 parts 1/2 "		
Drive	Spanner size:		
1/2"	27 mm		

KL-0186-1283 A Denso injector M16x1

2parts

Suitable for Denso injectors with a female thread M16x1 and a spanner size of 17 mm.

- Supplement for the injector extractor KL-0186-14 KB or KL-0186-80 K
- Depending on the engine, the specific support bolt kit

No. KL-0186-1283 A

• KL-0186-123.. / -124.. may be required









Spanner size: 17 mm

KL-0186-1282 A

Code

Siemens injector M27x1

Suitable for Siemens injectors with a female thread M27x1 and a spanner size of 27 mm.

- Supplement for the injector extractor KL-0186-14 KB or KL-0186-80 K
- Depending on the engine, the specific support bolt kit **KL-0186-123..** / **-124..** may be required



	"	
anner	size:	

Code	No.	for injectors	Drive	Spanner size:
3420140	KL-0186-1282 A	Siemens/VD0	1/2"	27 mm

for injectors

Denso

KL-0186-1285 A Delphi / Bosch injectors (90° angle)



Drive

Suitable for Delphi and Bosch injectors with lateral fuel connection (90° angle to the injector).

- Supplement for the injector extractor KL-0186-14 KB or KL-0186-80 K
- Depending on the engine, the specific support bolt kit **KL-0186-123..** / **-124..** may be required

Code	No.	for injectors	Engine type	Drive type	Weight
3420183	KL-0186-1285 A	Delphi and Bosch	Diesel	Mechanical / hydraulic / manual	600 g

UNIVERSAL GLOW PLUG TOOL KIT


















- Professional repair solution for torn glow plugs on the cylinder head
- For precise drilling out of the glow plug
- For pulling out the glow plug element
- For recutting the glow plug mounting thread
- No disassembly or replacement of the cylinder head
- Fast and precise work



NE	W

Code for thread No. For engine type M8x1 | M10x1 KL-0132-56 KC

Width / Height / Depth Storage

in case

Made in Germany

494 x 116 x 402 mm

Weight

5 kg

KL-0132-52 KB **GLOW PLUG TOOL KIT**

M10x1 universal





Fits universally for diesel engines with M10x1 glow plug thread, e.g. on VW-Audi, BMW, Mercedes, etc.

- For easily boring out torn glow plugs
- For recutting and cleaning the original thread on the cylinder head
- For pulling out the glow plug element
- Incl. particular guide sleeves for VW-Audi, BMW and Mercedes engines
- No need to remove or replace the cylinder head

for thread For engine type Storage Code No. KL-0132-52 KB M10x1 in case

KL-0132-55 KA

GLOW PLUG TOOL KIT

M8x1 universal







Made in Germany
















- For easily boring out torn glow plugs
- For recutting and cleaning the original thread on the cylinder head
- For pulling out the glow plug element
- Incl. particular guide sleeves for Mercedes and Fiat engines
- No need to remove or replace the cylinder head

Code	No.	For engine type	for thread	Storage
3431762	KL-0132-55 KA	Diesel	M8x1	in case

GLOW PLUG THREAD REPAIR KIT

(M8x1 + M10x1)



Fits universally for diesel engines with M8x1+ M10x1 glow plug thread.

- For the repair of damaged glow plug threads on the cylinder head
- No need to replace the cylinder head
- In combination with KL-0283-7021 A and KL-0283-7022 (KL-0132-52 KB)

for thread Storage Code No. For engine type KL-0132-57 K M8x1 | M10x1 in case

KL-0132-62 KB

22parts

GLOW PLUG TOOL KIT







7parts


M10x1.25 universal





Made in Germany





- For easily boring out torn glow plugs
- For recutting and cleaning the original thread on the cylinder head
- For pulling out the glow plug element
- No need to remove or replace the cylinder head

For engine type for thread Storage No. KL-0132-62 KB In plastic case

KL-1683-22 KA

GLOW PLUG TOOL KIT

Fiat, M8x1



















Suitable for Fiat, Alfa, Lancia 1.3 JTD (Euro 4) as well as 2.3 and 3.0 JTD / HDI Common-Rail Diesel engines with M8x1 mounting thread for glow plugs.

- For precise drilling out of torn and stuck glow plugs
- For recutting, cleaning or repairing the glow plug mounting
- The compressed air adapter prevents impurities from entering the combustion chamber

For engine type for thread Weight Code No. Diesel M8x1 KL-1683-22 KA 4.1 kg

KL-0369-300 A TURNING LATHE **OPERATOR**



















Suitable for electrodes with a diameter 2.5- 4.5 mm.

• For unscrewing the electrode head or the protruding middle electrode

Code	No.	For engine type	For Ø (min.)	For Ø max.	Drive (hexagon)	Length	Weight
2479184	KL-0369-300 A	Diesel	2.5 mm	4.5 mm	17.0 mm	70 mm	120 g

ASSEMBLY/DISASSEMBLY TOOL

Made in Germany















Universal fit.

- For forcing in and pressing out guide sleeves and centring
- In combination with glow plug tool kit KL-0132-52 KB.

Code	No.	For engine type	Length	Length of sliding surface	Impact weight
3431517	KL-0369-303 A	Diesel	280 mm	150 mm	800 g

KL-0369-5901

SEALING RING EXTRACTOR TIP















Universal fit for sealing rings with inner diameter of 3.5 - 14 mm.


- For removing sealing rings, e.g. injector sealing rings
- The conical tip is screwed into the sealing ring
- Only in conjunction with impact extractor KL-0049-101 A and KL-0049-100 A!



Code	No.	Length	Width	for Ø	Connection thread	Weight
243500	KL-0369-5901	84 mm	15 mm	3.5 - 10 mm	M10	50 g

KL-0049-100 A

IMPACT EXTRACTOR BASE UNIT

















- For pulling out stuck pieces like for example injection glow plugs, spindles etc.
- In combination with the individual adapters or tool kits

Code	No.	Impact weight	Length	Length of sliding surface	Connection thread	Weight
3423611	KL-0049-100 A	800 g	215 mm	150 mm	M10	1.1 kg
3423638	KL-0049-101 A	800 g	300 mm	235 mm	M10	1.3 kg

KL-0369-305 A

EXTRACTION TOOL FOR GLOW ELEMENT

















Universal fit.

- For pulling out the glow plug element
- In combination with glow plug tool kit KL-0132-52 KB.

	_				
Code	No.	For engine type	Drive (hexagon)	Connection thread (spindle)	Length
3431495	KL-0369-305 A	Diesel	19 mm	M12x1.25	185 mm



























KL-0369-201 A

GLOW PLUG EXTRACTION TOOL

Mercedes

Universal fit for diesel engines with M10x1 glow plug thread and a glow plug spanner size of 10 mm.

• For pulling out glow plugs that are still stuck in the bore



	Code	No.	Drive (hexagon)	For engine type	for thread	Length	Weight
ĺ	2479176	KL-0369-201 A	19 mm	Diesel	M10x1	135 mm	320 g

KL-0369-202

GLOW PLUG EXTRACTION TOOL

M8x1

Fits universally for diesel engines with M8x1 glow plug thread and a glow plug spanner size of 8 mm.

• For pulling out glow plugs that are still stuck in the bore

Made in Germany

Made in Germany





Code	No.	Drive (hexagon)	For engine type	for thread	Length	Weight
2968223	KL-0369-202	19 mm	Diesel	M8x1	135 mm	330 g

KL-0178-310 K

MOUNTING TOOL FOR SEALING FLANGE



Suitable for crankshaft sealing flanges with shaft seal ring and position encoder wheel with VW-Audi 1.0 + 1.5 TSI as well as 1.6 + 2.0 TDI engines.


- For professional assembly of the crankshaft sealing flange on the gearbox side.
- Exact pressing of the shaft sealing ring
- No errors in the engine control unit or leakage of the new sealing flange due to incorrect installation

Code	No.	For engine type	Storage	W/H/D
3444775	KL-0178-310 K	Petrol / Diesel	in case	391 mm / 134 mm / 304 mm

KL-0280-706 KA

LOCKING TOOL KIT VW (1.6, 2.0 TDI)





Fits with VW-Audi 1.4, 1.6 and 2.0 Common Rail diesel engines.

- For locking of the camshafts, crankshaft and high pressure
- For locking of the timing belt and V-ribbed belt tensioning

Code	No.	For engine type	Storage	Weight
3068846	KL-0280-706 KA	Diesel	in case	850 g

KL-0280-767 KB LOCKING TOOL KIT VW-Audi (1.2, 1.4)



Fits with VW-Audi 1.2 and 1.4 TSI/ FSI petrol engines.

- For locking of the camshafts, crankshaft, and V-ribbed belt tensioning unit
- For positioning the timing belt tensioning unit
- For pushing the timing belt in order to facilitate the tool

Code

No. KL-0280-767 KB For engine type

Storage





Weight

1.8 kg





KL-4051-310

IN-HEX SOCKET KIT

Polydrive M10





Universal fit.

- For unscrewing and tighten Polydrive M10 screw connections
- For cylinder head bolts and camshaft adjusters on VW-Audi engines

Code	No.	Profile	Drive (square)	Weight
3452956	KL-4051-310	M10 Polydrive	1/2"	250 g

KL-4077-10 K

ARTICULATED RING SPANNER KIT

Open, 150 mm

















Universally suitable for hard-to-reach line screw connections on the vehicle, e.g. on fuel systems, brake systems, hydraulic steering systems, exhaust systems and much more.

- For simple unscrewing and tightening line screw connections
- Extra-long, open spanner design with swivel head

Code	No.	Profile	Drive (square)	Length (chain sprocket)	Design	Swivel angle	Spanner sizes
345999	3 KL-4077-10 K	12-edge	3/8"	150 mm	open with joint	90°	12 / 13 / 14 / 17 / 19 / 22 mm















Universally applicable.

- For safe and quick filling of transmission, differential, engine, power steering, etc.
- The tank can be pressurised using the compressed air supply
- Both hands remain free for precise dosing during filling
- Manual operation possible using a manual feed pump
- Also suitable for very tight spaces or places that are difficult to access
- Incl. extensive range of adapters

Code	No.	Filling quantity	Working pressure (max.)	Drive type	Hose length	Weight
2871726	KL-0124-43	12 litres	2.5 bars	Manual / pneumatic	210 mm	5.9 kg

KL-0124-4360-1

ADAPTER, MERCEDES-BENZ 725.0

Suitable for Mercedes-Benz 9G-Tronic automatic gearbox (type 725.0).

- For professional draining and filling of the gearbox oil
- Only in conjunction with oil pump KL-0124-43









 Code
 No.
 Weight

 3445127
 KL-0124-4360-1
 160 g





ADAPTER, VW, DSG



Suitable for VW- Audi with 7-speed DSG gearbox (DL382 series) arranged longitudinally.

- For filling the gearbox
- Only in combination with KL-0124-43

Code	No.	Length	Width	Weight
3236935	KL-0124-4358-10	127 mm	22 mm	90 g



KL-0124-4359

ADAPTER angled

Suitable for VW-Audi with transversely arranged 7-speed DSG gearbox (DQ200 series).

- For filling the gearbox
- Only in combination with KL-0124-43

Code	No.	Length	Width	Height	Weight
3235556	KL-0124-4359	55 mm	36 mm	20 mm	90 g

A strong partnership in an increasingly complex working environment.

In a close technical exchange, we develop special solutions for and with SCHAEFFLER REPXPERT in the areas of clutch, drive, and chassis.

GEDORE customers get the jointly developed special tools in the genuine SCHAEFFLER REPXPERT case.



KL-0282-53 KA

TIMING CHAIN SPROCKET PULLER

VW 1.2 TSI

Fits VW-Audi, Seat, and Škoda with 1.2 TSI petrol engines. (Engine code: CBZA, CBZB, CBZC)

• Required for professional removal and mounting of the timing chain sprocket on the crankshaft

• For pushing the shaft seal ring in the control housing cover

- No lowering of the engine required
- Flywheel locking tool included

Suitability: VW AUDI SEAT SKODA



















Code	No.	Diameter	Length	Weight
3411524	KL-0282-53 KA	65 mm	240 mm	4.1 kg















KL-0500-80 KA (Code 3411664)

KLANN EXPERIENCE

GEDORE

DOUBLE CLUTCH BASIC TOOL KIT

Universal fit for VW-Audi, Seat, Škoda, Renault, and Ford PKW with dry double clutch systems.

- Enables the professional repair of *LuK** double clutch systems (dry clutch design)
- Only in combination with the vehiclespecific supplementary kits of the KL-0500-Series



KL-0500-81 KA (Code 3411648)

DOUBLE CLUTCH SUPPLEMENT FOR VW

Fits VW-Audi, Seat, and Škoda with dry double clutch systems, for example DSG gearboxes of the 1st or 2nd OAM generation.

- Enables the disassembly, assembly, and adjustment of dry double clutch systems
- Only in combination with KL-0500-80 KA basic tool



KL-0500-90 K (Code 3411591)

DOUBLE CLUTCH TOOL KIT FOR VW

Fits VW-Audi, Seat, and Škoda 7 geared double clutch gearbox (DQ250, DQ380, DQ381, DQ500) with wet clutch.

- For professional disassembly or installation and adjustment of double clutches
- Required, for example, when installing the LuK RepSet 2CT (602 0018 00 or 602 0022 00)



KL-0500-83 KA (Code 3411605)

DOUBLE CLUTCH SUPPLEMENT **FOR FORD**

Suitable for Ford with a dry double clutch system (e.g. DPS6 gearbox).

- Enables the disassembly, assembly, and adjustment of dry double clutch systems
- Only in combination with the KL-0500-80 KA basic tool kit



KL-0500-82 KA (Code 3411613)

DOUBLE CLUTCH SUPPLEMENT FOR RENAULT

Suitable for Renault with a dry double clutch system, e.g. DC4 gearbox.

- Enables the disassembly, assembly, and adjustment of dry double clutch systems
- Only in combination with the KL-0500-80 KA basic tool kit



KL-0500-71 KA (Code 3411702) **DOUBLE CLUTCH**

RESETTING TOOL

Fits Renault and Ford passenger cars with 6-speed double clutch gearboxes DC4 (Renault) and DPS6 (Ford).

- For professional resetting of the transport lock on the double clutch
- Required, if the double clutch is to be reused after the removal
- Only in combination with the KL-0500-80 KA basic tool kit



KL-0500-72 K (Code 3411672)

DOUBLE CLUTCH TOOL KIT FIAT (C635)

Fits Alfa Romeo, Fiat, Jeep, and Suzuki 6-speed double clutch gearbox (C635) with dry clutch.

- For professional disassembly or installation and adjustment of double clutches
- To reset the transport lock of an already used dual mass flywheel
- Required, for example, when installing the LuK RepSet 2CT (602 0003 00 or 602 0004 00)



KL-0500-61 KA (Code 3411540) DOUBLE CLUTCH SUPPLEMENTARY KIT

Enables the LuK double clutch special tool (LuK 400 0240 10) to be upgraded to the scope of delivery of the current double clutch basic tool kit KL-0500-80 KA and the double clutch supplement for VW KL-0500-81 KA.



DRIVE SHAFTS DISASSEMBLY LEVER





Blade width Weight Length Code No. KL-0414-2 40 mm 1.4 kg

KL-0880-10 K

MICRO VIDEOSCOPE

Ø 3.9 mm

Universally applicable on cars, vans, commercial vehicles, buses, construction machinery, agricultural machinery.













-10 up to +60 °C

5.000 mAh

No.

KL-0880-10 K

CLEANING VIDEOSCOPE

Universally applicable on cars, vans, commercial vehicles, buses, construction machinery, agricultural machinery.

- Enables the localisation and targeted removal of contamination.
- Versatile use on the vehicle, for example...
- ...for removing harmful and odour causing fungi, viruses, bacteria on the air conditioning evaporator in the heating or blower box.
- ...for loosening deposits and abrasion caused by DSG clutches, brake bands or synchroniser rings inside manual, automatic or differential gearboxes.
- ...to remove dirt build-up on water drains in the sill, water box, on the sunroof drain and
- ...for applying special cleaning solutions to clogged particulate filters (DPF), coked intake manifolds, EGR valves or dried-up Adblue® urea tanks.
- ...for cleaning dirty ventilation ducts and hard-to-reach seat frames for cleaning work in the vehicle interior.
- ...for flushing water and charge air coolers and much more
- The transversely mounted camera with LED lighting and cleaning nozzle also reaches hard-to-reach areas, e.g. the air conditioning evaporator
- Slim camera unit Ø 15 x 23 mm with powerful cleaning nozzle
- Dust- and water-proof lens with adjustable LED illumination
- For standard compressed air connection with 6 8 bar
- 250 ml container for cleaning fluids
- Live viewing via 3.5" colour display with zoom, rotate and mirror function
- Photo and video documentation with date/time stamp
- Direct playback of photos and videos on the display









before after

Code	No.	Display	Resolution	Cable diameter (max.)	Length, cable	Filling quantity	View angle	Operating pressure
344492	KL-0870-10 K	3.5"	720 x 625 pixels	23 mm	80 cm	250 ml	90°	6 - 8 bar



No. KL-0080-11 K

coaxial cable necessary

68parts

Code



KL-0080-20 K WIRING HARNESS REPAIR KIT Universally suitable for common cable/plug connections on vehicles and trailers. For connection with and without single conductor seal (ELA). • For professional maintenance of cable/plug connections • Comprehensive and robust range Application video • Can also be expanded in the future as required thanks to the interchangeable insert system • For damage-free release from the connector housing • For precise stripping, even for cables with slippery PVC insulation • Perfect crimping results as original • Crimping process must be exceuted completely in order to open the plier again NOTE: KL-0080-2 K - Wiring harness repair kit 19parts (Code 3464229) same as KL-0080-20 K but including consumables in i-Boxx Rack.

 Code
 No.
 for connector systems
 Stripping
 Crimping
 Crimping inserts
 Unlocking inserts

 3464202
 KL-0080-20 K
 MCP-2.8 (0.2-1.0 mm²) JPT (0.2-2.5 mm²) MQS (0.08-0.75 mm²)
 0.03 - 16 mm²
 0.35 - 6 mm² diameter
 9 pcs
 6 pcs

 DTM/DT twisted (0.5-2.1 mm²) SuperSeal-1.5 (0.35-2.5 mm²)
 2 pairs of blades
 / AWG 10 - 22

NOTE: Also available as KL-0080-10 K (code 3423026) and KL-0080-1 K (code 3429814), incl. two additional universal crimping heads.

MCP-2.8 (0.2-1.0 mm²) JPT (0.2-2.5 mm²) MQS (0.08-0.75 mm²) DTM/DT

twisted (0.5-2.1 mm²) SuperSeal-1.5 (0.35-2.5 mm²)



in i-Boxx

KL-0080-104 K

25 pcs

CRIMPING TOOL KIT

StreetScooter 5



Fits universally for "Micro 64" cable/plug connections. Installed in StreetScooter,

> • For professional maintenance of cable/plug connections

e.g. on the control unit or the parking lock.

- For damage-free release from the connector housing
- Perfect crimping results as original
- Crimping process must be completely executed in, order to open the pliers again

54parts Code

KL-0080-12 K

for connector systems

Crimping inserts:

Unlocking inserts

Made in Germany

Made in Germany

Quantity per contact

Storage

in case

KL-0080-123

SUPPLEMENTARY KIT MICRO 64







Fits universally for "Micro 64" cable/plug connections (0.35- 0.8 mm²).

- Installed in StreetScooter
- In combination with KL-0080-1 K / -10 K

Code

No.

KL-0080-123

for connector systems

Micro 64 (0,35-0,8 mm²)

KL-0080-130

SUPPLEMENTARY KIT MICROTIMER







Made in Germany



- Mounted on various sensors and actuators, e.g. camshaft sensor, lighting, wear indicator
- For connection with and without single conductor seal (ELA)
- In combination with KL-0080-1 K / -10 K

278parts

Code

No.

KL-0080-130

for connector systems

MicroTimer 2/3 (0.2-1.0 mm²)

KL-0080-131

SUPPLEMENTARY KIT MCP 1.5K







Made in Germany



- Installed in various sensors, actuators, and control units, e. g. engine control unit, gearbox control unit, comfort control
- For connection with and without single conductor seal (ELA)
- In combination with KL-0080-1 K / -10 K

Code

No. KL-0080-131 for connector systems

MCP 1.5K (0.2-1.5 mm²)

TOOL TROLLEY


with high voltage assortment

- The perfect tool kit for maintenance and repairs on hybrid and electric vehicles
- Suitable for vehicles of all manufacturers
- All tools are protective insulated to EN 60900/EC 60900
- Tool trolley: Side walls with Euro perforation, externally mounted heavy- duty ball-bearing guide rails and central lock
- Including: digital voltage tester, 3/8" VDE torque wrench, safety lock, socket spanner with ratchet in 3/8" and 1/2", and many more.

Content:

- 3/8" VDE tool assortment with SW 6 22; XZN M8 M12
- 3/8" VDE torque wrench 5 25 Nm
- 1/2" VDE workshop assortment with SW 10 24; IN 5 8 mm;
- VDE single open-end spanner SW 9 24
- VDE single end ring spanner SW 8 22
- VDE slotted and cross-head screwdriver; TX T8 T30
- VDE cable shear, VDE universal pliers, VDE power combination pliers, VDE power diagonal cutter, VDE flat nose-round pliers, angled, VDE flat pliers, VDE cable stripping knife
- Safety padlock
- Digital voltage tester 1,000 V
- Electrician's protective gloves
- Undergloves
- Rubberised cloth cover 250 x 350 mm
- ISO insulation mat
- Barrier tape
- Warning sign "Flash"
- Warning sign high voltage "Switched ON", Warning sign "Switched OFF"





Made in Germany



Code	No.	Dimensions	Number of drawers	Load capacity (mobile/static)	Load capacity (per drawer)	Design
3415740	KL-4600-200	H 985 x W 775 x D 475 mm		650 kg / 900 kg	40 kg	3/8" + 1/2"

Made in Germany

KL-4600-10 Z

VDE HYBRID TOOL

incl. supplement

Fits universally for hybrid and electric vehicles.

- Perfect tool kit for maintenance and repairs on hybrid and electric vehicles
- Suitable for vehicles of all manufacturers
- All tools are protective insulated to EN 60900/EC 60900
- With digital HV voltage tester and safety padlock
- Incl. empty compartment or VDE torque wrench 4508-02/-05

Content:

- 3/8" VDE socket spanner no. VDE 30, SW 6 8 9 10 11 12 13 14 15 16 17 18 19 20 22 mm
- 3/8" VDE screwdriver bit no. VDE INX 30, SW 8 10 12 mm
- 3/8" VDE extension no. VDE 3090 -3 -6, 75 150 mm
- 3/8" VDE reversible ratchet no. VDE 3093 U
- VDE slotted screwdriver no. VDE 2170, 2.5 3.5 4 5.5 mm
- \bullet VDE cross-head screwdriver no. VDE 2160 PH 1 2 3
- \bullet VDE screwdriver TX no. VDE 2163 TX T20 T25 T30
- VDE cable shear no. VDE 8094, 200 mm
- VDE universal pliers fitting no. VDE 146 10, 10"
- VDE power combination pliers no. VDE 8250-200 H, 200 mm 2K-handle
- \bullet VDE power diagonal cutter no. VDE 8314-180 H, 180 mm
- VDE flat nose-round pliers no. VDE 8132 AB-200 JC, 200 mm angled 2K handle
- VDE flat pliers no. VDE 8120-160 H, 160 mm 2K handle
- VDE cable stripping knife no. VDE 4522, 180 mm
- Meter connection fitting no. V 914, size 1 2 3
- Digital voltage tester 1.000 V
- Protective gloves for electricians



Code No. Consisting of

3418642 KL-4600-10 Z KL-4600-100 K VDE supplementary kit and 1100-1094 VDE HYBRID tool kit



THE PROFESSIONAL ALL INCLUSIVE PACKAGE

KL-4998-400

WORKSHOP TROLLEY

Hand tool for passenger cars

Universally applicable when performing maintenance and repair work on cars and vans.

- Very extensive and extremely robust hand tool assortment
- · Ideal, mobile workplace
- Metric design
- 8 fully equipped drawers
- One empty drawer at the very bottom
- Broad drawers with full-extension runners
- · Safety locking per drawer




You will find the same range in the extra-wide XL trolley on the back.













GEDORE

412parts





Code

No.

KL-4998-400

Number of drawers

9 (hottom empty)

Drawer dimensions

Load-carrying capacity of drawers 40 kg (lowest 60 kg) Trolley dimensions
H 812 x W 771 x D 478 mm

Total load carrying capacity (static/mobile)
1,000 kg / 750 kg

GEDORE**▼**red













Rodv.

- Sheet steel, corrosion and scratch-resistant, powder-coated
- Work platform with ABS plastic cover with 4 small parts compartments

TOOL SET IN WORKSHOP TROLLEY

- Manoeuvrable and easy to steer with drive/steer handle
- Side walls with Euro perforation 10 x 38 mm for attaching accessories

Drawers:

• Central locking with cylinder lock

GEDMaster 273 pcs.

- Safety locking per drawer, one-hand operation
- 5 drawers with internal dimensions (W 563 x D 398 x 70 mm)
- 2 drawers with internal dimensions (W 563 x D 398 x 145 mm)
- All drawers with full-extension runners with ball bearings
- Load-bearing capacity per drawer 40 kg

• GEDORE chassis:

- Total load capacity 400 kg
- 2 GEDORE heavy-duty wheels with roller bearings (fixed castors, 140 mm)
- 2 GEDORE easy-running wheels with ball bearings (swivel castors, 100 mm), one of them with total brake each
- The GEDORE trapezoidal axle design ensures even at maximum load: smooth running, manoeuvrability, and directional stability

• Assortment:

- Extensive assortment for industry, trade, automotive and the advanced handyman
- Tools in metric dimensions
- Clearly arranged in GEDORE black foam inlay
- With checking tool system: Completeness check due to 2 coloured foam inserts













DOUBLE ARTICULATED RATCHET RING

SPANNER SET

Universal fit for E profile (Torx[®]) screws.

- For unscrewing and tightening of hard-to-access screws
- Highly durable with joint heads on both sides
- Small return angle thanks to fine-toothed design



4parts

Code	No.	Ring profile	Spanner sizes	Design	Swivel angle	Storage
3438147	KL-4443-30	Inner-TX	E6/8, E10/12, E14/18, E20/24	with joint	180°	Plastic holder





OFFSET ALLEN KEY SET

hexagon 1.5-10mm 9 pcs





- Round shape
- Long version with ball head
- Matt chrome-plated
- Folding holder with belt clip

Code	No.	Profile	Spanner size:	Design	Weight
3301332	R36601009	6-edge	1.5 – 10 mm	Long with ball head	600 g

R36401009

OFFSET ALLEN KEY SET

TX T10-T50 9 pcs



GEDORE red ○

GEDORE ▼ red









- Colour coding for quicker identification of the correct allen key size
- Round shape
- Long version
- Matt chrome-plated
- Folding holder with belt clip

Code	No.	Profile	Spanner size:	Design	Weight
3301332	R36401009	TX	T10 – T50	Long	600 g

























KL-4911-102

CAN HOLDER magnetic

Universally applicable.




Code	No.	For Ø max.	Magnet load	Weight
3457125	KL-4911-102	70 mm	3000	290 g

KL-4911-103

MAGNETIC TRAY

Universally applicable.







KL-4991-101

SILICONE STORAGE MAT



Universally applicable.

- For safe storage of tools, screws and small parts
- Flexible and non-slip surface
- Easy to place directly on the vehicle
- Extremely secure hold
- · Clearly organised storage
- With two removable compartments
- Also suitable for delicate surfaces
- Easy to clean, water and oil resistant









Mat 1



3parts

Code No. Mat 1 size (L/W/H)

Mat 2 size (L/W/H)

Mat 3 size (L/W/H)

262 x 232 x 25 mm

Total weight 2.5 kg

KL-4911-11...

MAGNETIC MAT





Universally suitable for cars, commercial vehicles, and

- For safe storage and fixing of tools, screws, etc.
- Extremely powerful magnet
- Easy to attach to any magnetic surface
- Can also be used on non-magnetic surfaces
- Structured, padded plastic surface
- Also suitable for delicate surfaces
- Easy to clean, water and oil resistant





Code	No.	Dimensions	Colour	Weight
3457168	KL-4911-111	114 x 114 mm	black	100 g
3457176	KL-4911-112	280 x 200 mm	black	400 g
3457184	KL-4911-113	305 x 50 mm	black	130 g

KL-4080-100

SOCKETS, MAGNETIC SW10 up to SW19





For universal use in everyday workshop repair work.

- For inserting into conventional sockets
- For securely holding nuts and bolts
- With high holding force
- For hexagon and double hexagon sockets
- For spanner widths from 10 to 19 mm

Code	No.	for profile	Content	Weight
3468941	KL-4080-100	Hexagon/ double hexagon	10	35 g



KL-0194-190

SET OF PLASTIC WEDGES















Universally suitable for cars, commercial vehicles, and

- For gentle disassembly of trims, coverings, switches, seals,
- Many different profiles
- Robust, fibre-reinforced nylon plastic
- In a well-organised storage bag



Code	No.	Length	Storage	Weight
3457087	KL-0194-190	180 mm	Foldable bag	1.2 kg

90020

LI-MH LED LAMP USB CHARGING PORT















- Versatile LED/UV lamp with a slim design
- Infinitely dimmable, switchable from LED light to UV light blue-violet
- For finding leaks, for example in air conditioning systems, heat pumps, etc.
- Hooks can be folded out on both sides, powerful magnet on the 45° adjustable base
- Powerful mini magnet at the peak for collecting small parts
- Can be charged by the supplied power pack or a USB port

Code	No.	Length	Brightness	Lamp power	Battery
3108678	900 20	477 mm	620 lumen	16 W	3.350 mAh



R95300139

PENLIGHT

- Compact, slim size
- Protected against the intrusion of small dust particles and splash water
- Good grip even with oily and sweaty hands
- Can also be used with gloves
- Mobile companion for all applications • Practical clip for attaching to belt, shirt or trouser pocket



Code	No.	Length	Ø	Burn time	Battery type	Battery quantity
3301758	R95300139	139 mm	15 mm	4 h	AAA	2 pcs

GEDORE Fred (Q

R95700089

MINI WORK LAMP

- Extremely bright lamp in a very compact format
- Can be used especially in confined spaces
- Magnet provides different holding options in different working areas
- Enables hands-free working
- Mobile companion for all applications
- Practical clip for attaching to belt, shirt or trouser pocket
- Fits in every trouser pocket



1	Code	No.	Length	Burn time	Battery capacity	Charging time
	3301759	R95700089	89 mm	3 h	600 mAh	2.5 h



SPOTLIGHT

• Compact, portable spotlight

• Ideal for working in places without power

• Rubberised surround, therefore shockproof

• Stand can also be hung up or used as a carrying handle • Easy alignment of the light • Power bank function for charging

R95400145

supply

and splashproof

• 180° rotatable base

external devices


















R95600320

INSPECTION LAMP

- Ideal as a work lamp for mobile use in various areas
- 5 switching functions for individually adjustable brightness
- Can be used both as an inspection lamp and as a torch
- Magnet and 180° rotating hook provide different holding options
- Enables flexible and mobile use, as well as hands-free working





Code Width Burn time Battery capacity Charging time No. R95400145 145 mm 4.400 mAh





- Stainless steel Blade lock
- Ergonomic handle, hand-friendly power transmission



Weight Code No. R99800000

KLM-0101

EXPERIENCE T-SHIRT

- Stretch jersey (190 g/m²): 95% cotton / 5% Elasthane
- Oeko-Tex® Standard 100
- Manufactured under fair working conditions
- Applications on chest and arm



Code	No.	Size
3418758	KLM-0101-S	S
3419355	KLM-0101-M	M
3419363	KLM-0101-L	L
3419371	KLM-0101-XL	XL
3419398	KLM-0101-XXL	XXL



KLM-0202

MKP LONGSLEEVE

- 100% Organic cotton (220 g/m²)
- Manufactured under fair working conditions
- Applications on chest, back, and arm



Code	No.	Size
3419401	KLM-0202-S	S
3419428	KLM-0202-M	M
3419436	KLM-0202-L	and the second second
3419444	KLM-0202-XL	XL
3419452	KLM-0202-XXL	XXL



KLM-0402

MPK SOFTSHELL WAISTCOAT

- Breathable with permanently water-repellent coating
- Windproof three-layer membrane fabric
- Zipped pockets, adjustable elasticated hem
- Manufactured under fair working conditions
- Application on the front



	_	
Code	No.	Size
3419517	KLM-0402-S	S
3419533	KLM-0402-M	M
3419541	KLM-0402-L	L
3419576	KLM-0402-XL	XL
3419584	KLM-0402-XXL	XXL



2005 XL-S-466

WORKSHOP TOOL TROLLEY with passenger car assortment

- Fully equipped tool trolley for fast, organised and efficient repair and maintenance work in everyday workshop life
- Tools in metric dimensions
- With GEDORE checking tool system: Completeness check due to 2 coloured foam inserts
- Resistant against oils and grease
- In the tool trolley no. 2005 XL with 8 drawers
- Total load capacity 1000 kg static, 750 kg dynamic
- 8 extra wide drawers (W 792 x D 400 mm)
- Load capacity per drawer 60 kg, lower heavy-duty drawer 70 kg
- Chassis: The GEDORE trapezoidal axle design ensures even at maximum load: smooth running, manoeuvrability, and directional stability





Drawer dimension

B 792 x T 400 mm

40 kg (lowest 60 kg)

Your dealer/stamp:

2005 XL-S-466



Weight

165 kg

Total load carrying capacity (static/mobile)

1,000 kg / 750 kg

SOLUTION5 NEWS + PROMOTION valid from 01.01. – 31.08.2024 Only while stocks last.

Delivery without decoration.
Subject to technical changes.
All information are subject to typographical and printing errors.

GEDORE Automotive GmbH

Breslauer Straße 41 | 78166 Donaueschingen | GERMANY Phone +49 +4977183223-0| info.gam@gedore.com